

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

SECTION 1. PRODUCT AND COMPANY IDENTIFICATION

Product name : DOS Bearing Retainer High Strength

Product code : 0893 603 050

Manufacturer or supplier's details

Company : Wurth Australia Pty Ltd

Address : 2/1 Healey Road
Dandenong South, Victoria, 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National Poisons Centre: 131 126

E-mail address : prodsafe@wuerth.com

Recommended use of the chemical and restrictions on use

Recommended use : Adhesives

SECTION 2. HAZARDS IDENTIFICATION**GHS Classification**

Flammable liquids : Category 4

Skin sensitisation : Category 1

Skin corrosion/irritation : Category 2

Serious eye damage/eye irritation : Category 1

Specific target organ toxicity - single exposure : Category 3

GHS label elements

Hazard pictograms :



Signal word : Danger

Hazard statements : H227 Combustible liquid.
H315 Causes skin irritation.
H317 May cause an allergic skin reaction.

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
 Date of first issue: 06.10.2010

H318 Causes serious eye damage.
 H335 May cause respiratory irritation.

Precautionary statements :

Prevention:

P210 Keep away from heat/ sparks/ open flames/ hot surfaces. No smoking.
 P261 Avoid breathing mist or vapours.
 P264 Wash skin thoroughly after handling.
 P271 Use only outdoors or in a well-ventilated area.
 P272 Contaminated work clothing should not be allowed out of the workplace.
 P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.
 P305 + P351 + P338 + P310 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Immediately call a POISON CENTER or doctor/ physician.
 P333 + P313 If skin irritation or rash occurs: Get medical advice/ attention.
 P362 Take off contaminated clothing and wash before reuse.

Storage:

P403 + P235 Store in a well-ventilated place. Keep cool.
 P405 Store locked up.

Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

Other hazards which do not result in classification

Vapours may form explosive mixture with air.

SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

Components

| Chemical name | CAS-No. | Concentration (% w/w) |
|---|------------|-----------------------|
| Methacrylic acid, monoester with propane-1,2-diol | 27813-02-1 | >= 30 -< 60 |
| Acrylic acid | 79-10-7 | >= 3 -< 5 |
| Cumene hydroperoxide | 80-15-9 | < 1 |
| 2'-Phenylacetohydrazide | 114-83-0 | < 1 |

SECTION 4. FIRST AID MEASURES

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.
Get medical attention.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.
Get medical attention.
Wash clothing before reuse.
Thoroughly clean shoes before reuse.
- In case of eye contact : In case of contact, immediately flush eyes with plenty of water for at least 15 minutes.
If easy to do, remove contact lens, if worn.
Get medical attention immediately.
- If swallowed : If swallowed, DO NOT induce vomiting.
Get medical attention.
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.
May cause an allergic skin reaction.
Causes serious eye damage.
May cause respiratory irritation.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
-

SECTION 5. FIREFIGHTING MEASURES

- Suitable extinguishing media : Water spray
Alcohol-resistant foam
Carbon dioxide (CO₂)
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Do not use a solid water stream as it may scatter and spread fire.
Flash back possible over considerable distance.
Vapours may form explosive mixtures with air.
Exposure to combustion products may be a hazard to health.
- Hazardous combustion products : Carbon oxides

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.
Use water spray to cool unopened containers.
Remove undamaged containers from fire area if it is safe to do so.
Evacuate area.
- Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.
Use personal protective equipment.
-

SECTION 6. ACCIDENTAL RELEASE MEASURES

- Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.
Use personal protective equipment.
Follow safe handling advice (see section 7) and personal protective equipment recommendations (see section 8).
- Environmental precautions : Avoid release to the environment.
Prevent further leakage or spillage if safe to do so.
Prevent spreading over a wide area (e.g. by containment or oil barriers).
Retain and dispose of contaminated wash water.
Local authorities should be advised if significant spillages cannot be contained.
- Methods and materials for containment and cleaning up : Non-sparking tools should be used.
Soak up with inert absorbent material.
Suppress (knock down) gases/vapours/mists with a water spray jet.
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.
Clean up remaining materials from spill with suitable absorbent.
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.
-

SECTION 7. HANDLING AND STORAGE

- Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.
- Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.
- Advice on safe handling : Do not get on skin or clothing.
Avoid breathing mist or vapours.
Do not swallow.
Do not get in eyes.
-

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
 Date of first issue: 06.10.2010

Wash skin thoroughly after handling.
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment
 Keep container tightly closed.
 Already sensitised individuals should consult their physician regarding working with respiratory irritants or sensitisers.
 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
 Take precautionary measures against static discharges.
 Take care to prevent spills, waste and minimize release to the environment.

- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.
 When using do not eat, drink or smoke.
 Contaminated work clothing should not be allowed out of the workplace.
 Wash contaminated clothing before re-use.
- Conditions for safe storage : Keep in properly labelled containers.
 Store locked up.
 Keep tightly closed.
 Keep in a cool, well-ventilated place.
 Store in accordance with the particular national regulations.
 Keep away from heat and sources of ignition.
- Materials to avoid : Do not store with the following product types:
 Strong oxidizing agents

SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Components with workplace control parameters

| Components | CAS-No. | Value type (Form of exposure) | Control parameters / Permissible concentration | Basis |
|--------------|--------------------------------------|----------------------------------|--|--------|
| Acrylic acid | 79-10-7 | TWA | 2 ppm 5.9 mg/m ³ | AU OEL |
| | Further information: Skin absorption | | | |
| | | TWA | 2 ppm | ACGIH |

- Engineering measures** : Minimize workplace exposure concentrations.
 If sufficient ventilation is unavailable, use with local exhaust ventilation.

Personal protective equipment

- Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.
- Filter type : Combined particulates and organic vapour type

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Hand protection

Material : Nitrile rubber
Break through time : > 480 min
Glove thickness : > 0.35 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:
Chemical resistant goggles must be worn.
If splashes are likely to occur, wear:
Face-shield

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.
Wear the following personal protective equipment:
If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.
Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : liquid

Colour : green

Odour : characteristic

Odour Threshold : No data available

pH : 4
Concentration: 10 %
No data available

Melting point/freezing point : No data available

Initial boiling point and boiling range : No data available

Flash point : > 90 °C

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

| | | |
|--|---|--|
| Evaporation rate | : | No data available |
| Flammability (solid, gas) | : | Not applicable |
| Flammability (liquids) | : | Ignitable (see flash point) |
| Upper explosion limit / Upper flammability limit | : | No data available |
| Lower explosion limit / Lower flammability limit | : | No data available |
| Vapour pressure | : | No data available |
| Relative vapour density | : | No data available |
| Relative density | : | No data available |
| Density | : | 1.07 g/cm ³ (25 °C) |
| Solubility(ies) | | |
| Water solubility | : | partly miscible |
| Partition coefficient: n-octanol/water | : | Not applicable |
| Auto-ignition temperature | : | No data available |
| Decomposition temperature | : | No data available |
| Viscosity | | |
| Viscosity, dynamic | : | 100 - 200 mPa.s (25 °C) Method: Brookfield |
| Viscosity, kinematic | : | No data available |
| Explosive properties | : | Not explosive |
| Oxidizing properties | : | The substance or mixture is not classified as oxidizing. |
| Particle size | : | Not applicable |

SECTION 10. STABILITY AND REACTIVITY

| | | |
|------------------------------------|---|--|
| Reactivity | : | Not classified as a reactivity hazard. |
| Chemical stability | : | Stable under normal conditions. |
| Possibility of hazardous reactions | : | Combustible liquid. Vapours may form explosive mixture with air. Can react with strong oxidizing agents. |

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

| | | |
|----------------------------------|---|--|
| Conditions to avoid | : | Heat, flames and sparks. |
| Incompatible materials | : | Oxidizing agents |
| Hazardous decomposition products | : | No hazardous decomposition products are known. |

SECTION 11. TOXICOLOGICAL INFORMATION

| | | |
|-----------------|---|--|
| Exposure routes | : | Inhalation Skin contact Ingestion Eye contact |
|-----------------|---|--|

Acute toxicity

Not classified based on available information.

Product:

| | | |
|---------------------------|---|---|
| Acute oral toxicity | : | Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method |
| Acute inhalation toxicity | : | Acute toxicity estimate: > 20 mg/l Exposure time: 4 h Test atmosphere: vapour Method: Calculation method |
| Acute dermal toxicity | : | Acute toxicity estimate: > 2,000 mg/kg Method: Calculation method |

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

| | | |
|-----------------------|---|---|
| Acute oral toxicity | : | LD50 (Rat): > 2,000 mg/kg Method: OECD Test Guideline 401 Assessment: The substance or mixture has no acute oral toxicity |
| Acute dermal toxicity | : | LD50 (Rabbit): > 5,000 mg/kg |

Acrylic acid:

| | | |
|---------------------------|---|--|
| Acute oral toxicity | : | LD50 (Rat): 357 mg/kg |
| Acute inhalation toxicity | : | LC50 (Rat): > 5.1 mg/l Exposure time: 4 h Test atmosphere: vapour |
| Acute dermal toxicity | : | LD50 (Rabbit): > 2,000 mg/kg Method: OECD Test Guideline 402 Assessment: The substance or mixture has no acute dermal toxicity |

Cumene hydroperoxide:

| | | |
|---------------------|---|-----------------------------|
| Acute oral toxicity | : | LD50 (Rat, male): 382 mg/kg |
|---------------------|---|-----------------------------|

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Acute inhalation toxicity : Acute toxicity estimate: 3 mg/l
Exposure time: 4 h
Test atmosphere: vapour
Method: Expert judgement
Remarks: Based on harmonised classification in EU regulation 1272/2008, Annex VI

Acute dermal toxicity : LD50 (Rabbit, male): 133.6 mg/kg

2'-Phenylacetohydrazide:

Acute oral toxicity : LD50 (Mouse): 270 mg/kg

Acute dermal toxicity : LD50 (Rabbit): > 300 - 2,000 mg/kg
Remarks: Based on data from similar materials

Skin corrosion/irritation

Causes skin irritation.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Species : Rabbit
Result : No skin irritation

Acrylic acid:

Species : Rabbit
Method : OECD Test Guideline 404
Result : Corrosive after 3 minutes or less of exposure

Cumene hydroperoxide:

Species : Rabbit
Result : Corrosive after 4 hours or less of exposure

2'-Phenylacetohydrazide:

Species : Rabbit
Result : Skin irritation
Remarks : Based on data from similar materials

Serious eye damage/eye irritation

Causes serious eye damage.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days

Acrylic acid:

Species : Rabbit
Result : Irreversible effects on the eye

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Cumene hydroperoxide:

Species : Rabbit
Result : Irreversible effects on the eye

2'-Phenylacetohydrazide:

Species : Rabbit
Result : Irritation to eyes, reversing within 21 days
Remarks : Based on data from similar materials

Respiratory or skin sensitisation**Skin sensitisation**

May cause an allergic skin reaction.

Respiratory sensitisation

Not classified based on available information.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Species : Guinea pig
Result : positive

Assessment : Probability or evidence of skin sensitisation in humans

Acrylic acid:

Test Type : Freund's complete adjuvant test
Exposure routes : Skin contact
Species : Guinea pig
Result : negative

Chronic toxicity**Germ cell mutagenicity**

Not classified based on available information.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Method: OECD Test Guideline 471
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo
cytogenetic assay)
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 474
Result: negative

Acrylic acid:

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test
Result: negative

Genotoxicity in vivo : Test Type: Rodent dominant lethal test (germ cell) (in vivo)
Species: Mouse
Application Route: Ingestion
Result: negative

Cumene hydroperoxide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Test Type: DNA damage and repair, unscheduled DNA synthesis in mammalian cells (in vitro)
Result: positive

Test Type: Chromosome aberration test in vitro
Result: positive

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)
Species: Mouse
Application Route: Skin contact
Result: negative

2'-Phenylacetohydrazide:

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)
Result: positive

Carcinogenicity

Not classified based on available information.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Species : Rat
Application Route : Inhalation
Exposure time : 102 weeks
Result : negative

Acrylic acid:

Species : Mouse
Application Route : Skin contact
Exposure time : 21 Months
Result : negative

2'-Phenylacetohydrazide:

Species : Mouse
Application Route : Ingestion
Exposure time : 2 years
Result : positive

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Carcinogenicity - Assessment : Limited evidence of carcinogenicity in animal studies (oral)

Reproductive toxicity

Not classified based on available information.

Components:**Methacrylic acid, monoester with propane-1,2-diol:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 422
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rabbit
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

Acrylic acid:

Effects on fertility : Test Type: Two-generation reproduction toxicity study
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 416
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: inhalation (vapour)
Method: OECD Test Guideline 414
Result: negative

Cumene hydroperoxide:

Effects on foetal development : Test Type: Embryo-foetal development
Species: Rat
Application Route: Ingestion
Method: OECD Test Guideline 414
Result: negative

STOT - single exposure

May cause respiratory irritation.

Components:**Acrylic acid:**

Assessment : May cause respiratory irritation.

Cumene hydroperoxide:

Assessment : May cause respiratory irritation.

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

STOT - repeated exposure

Not classified based on available information.

Components:**Cumene hydroperoxide:**

Exposure routes : Inhalation
Target Organs : Lungs
Assessment : Shown to produce significant health effects in animals at concentrations of >0.2 to 1 mg/l/6h/d.

Repeated dose toxicity**Components:****Methacrylic acid, monoester with propane-1,2-diol:**

Species : Rat
NOAEL : ≥ 300 mg/kg
Application Route : Ingestion
Exposure time : 49 Days
Method : OECD Test Guideline 422

Acrylic acid:

Species : Rat
NOAEL : 40 mg/kg
LOAEL : 100 mg/kg
Application Route : Ingestion
Exposure time : 12 Months

Aspiration toxicity

Not classified based on available information.

SECTION 12. ECOLOGICAL INFORMATION**Ecotoxicity****Components:****Methacrylic acid, monoester with propane-1,2-diol:**

Toxicity to fish : LC50 (Leuciscus idus (Golden orfe)): 493 mg/l
Exposure time: 48 h
Method: DIN 38412

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 143 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Pseudokirchneriella subcapitata (green algae)): > 97.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

NOEC (Pseudokirchneriella subcapitata (green algae)): >= 97.2 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 45.2 mg/l
Exposure time: 21 d
Method: OECD Test Guideline 211

Toxicity to microorganisms : EC10 (Pseudomonas putida): 1,140 mg/l

Acrylic acid:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 27 mg/l
Exposure time: 96 h

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 95 mg/l
Exposure time: 48 h

Toxicity to algae/aquatic plants : EC50 (Scenedesmus subspicatus): 0.205 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

EC10 (Scenedesmus subspicatus): 0.031 mg/l
Exposure time: 72 h
Method: Directive 67/548/EEC, Annex V, C.3.

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 3.8 mg/l
Exposure time: 21 d

Toxicity to microorganisms : NOEC: 100 mg/l
Exposure time: 30 min
Method: ISO 8192

Cumene hydroperoxide:

Toxicity to fish : LC50 (Oncorhynchus mykiss (rainbow trout)): 3.9 mg/l
Exposure time: 96 h
Method: OECD Test Guideline 203

Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): 18.84 mg/l
Exposure time: 48 h
Method: OECD Test Guideline 202

Toxicity to algae/aquatic plants : ErC50 (Desmodesmus subspicatus (green algae)): 3.1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

NOEC (Desmodesmus subspicatus (green algae)): 1 mg/l
Exposure time: 72 h
Method: OECD Test Guideline 201

2'-Phenylacetohydrazide:

Toxicity to fish : LC50 (Brachydanio rerio (zebrafish)): > 0.1 - 1 mg/l

DOS Bearing Retainer High Strength

Version 8.0 Revision Date: 18.12.2020 SDS Number: 587220-00007 Date of last issue: 11.11.2020
Date of first issue: 06.10.2010

Exposure time: 96 h
Remarks: Based on data from similar materials

Persistence and degradability**Components:****Methacrylic acid, monoester with propane-1,2-diol:**

Biodegradability : Result: Readily biodegradable.
Biodegradation: 81 %
Exposure time: 28 d
Method: OECD Test Guideline 301C

Acrylic acid:

Biodegradability : Result: Readily biodegradable.
Biodegradation: 68 %
Exposure time: 14 d
Method: OECD Test Guideline 301

Cumene hydroperoxide:

Biodegradability : Result: Not readily biodegradable.
Biodegradation: 3 %
Exposure time: 28 d
Method: OECD Test Guideline 301B

2'-Phenylacetohydrazide:

Biodegradability : Result: Readily biodegradable.
Remarks: Based on data from similar materials

Bioaccumulative potential**Components:****Methacrylic acid, monoester with propane-1,2-diol:**

Partition coefficient: n-octanol/water : log Pow: 0.97

Acrylic acid:

Partition coefficient: n-octanol/water : log Pow: 0.46

Cumene hydroperoxide:

Partition coefficient: n-octanol/water : log Pow: 1.6
Method: OECD Test Guideline 117

Mobility in soil

No data available

Other adverse effects

No data available

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

SECTION 13. DISPOSAL CONSIDERATIONS**Disposal methods**

- Waste from residues : Dispose of in accordance with local regulations.
- Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.
Empty containers retain residue and can be dangerous.
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.
If not otherwise specified: Dispose of as unused product.
-

SECTION 14. TRANSPORT INFORMATION**International Regulations****UNRTDG**

Not regulated as a dangerous good

IATA-DGR

- UN/ID No. : UN 3334
Proper shipping name : Aviation regulated liquid, n.o.s.
(Acrylic acid)
Class : 9
Packing group : III
Labels : Miscellaneous
Packing instruction (cargo aircraft) : 964
Packing instruction (passenger aircraft) : 964

IMDG-Code

Not regulated as a dangerous good

Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code

Not applicable for product as supplied.

National Regulations**ADG**

Not regulated as a dangerous good

Special precautions for user

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

SECTION 15. REGULATORY INFORMATION

Safety, health and environmental regulations/legislation specific for the substance or mixture

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

Standard for the Uniform Scheduling of Medicines and Poisons : No poison schedule number allocated

Prohibition/Licensing Requirements : There is no applicable prohibition, authorisation and restricted use requirements, including for carcinogens referred to in Schedule 10 of the model WHS Act and Regulations.

The components of this product are reported in the following inventories:

AIIC : All ingredients listed or exempt.

SECTION 16. OTHER INFORMATION

Further information

Revision Date : 18.12.2020

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Items where changes have been made to the previous version are highlighted in the body of this document by two vertical lines.

Date format : dd.mm.yyyy

Full text of other abbreviations

ACGIH : USA. ACGIH Threshold Limit Values (TLV)
 AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.

ACGIH / TWA : 8-hour, time-weighted average
 AU OEL / TWA : Exposure standard - time weighted average

AIIC - Australian Inventory of Industrial Chemicals; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median

DOS Bearing Retainer High Strength

| | | | |
|---------|----------------|--------------|---------------------------------|
| Version | Revision Date: | SDS Number: | Date of last issue: 11.11.2020 |
| 8.0 | 18.12.2020 | 587220-00007 | Date of first issue: 06.10.2010 |

Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - United Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN