

**HHS Lube 500ml**

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
Date of first issue: 29.09.2010

---

**SECTION 1. PRODUCT AND COMPANY IDENTIFICATION**

Product name : HHS Lube 500ml

Product code : 0893 106 5

**Manufacturer or supplier's details**

Company : Wurth Australia Pty Ltd

Address : 2/1 Healey Road  
Dandenong South, Victoria, 3175

Telephone : +61 3 8788 1111

Emergency telephone number : 1300 657 765. Advisory office in case of poisoning - National Poisons Centre: 131 126

E-mail address : prodsafe@wurth.com

**Recommended use of the chemical and restrictions on use**

Recommended use : Lubricants and lubricant additives  
Compressed Gas (Aerosol cans)

---

**SECTION 2. HAZARDS IDENTIFICATION****GHS Classification**

Flammable aerosols : Category 1

Skin corrosion/irritation : Category 2

Specific target organ toxicity - single exposure : Category 3

**GHS label elements**

Hazard pictograms :



Signal word : Danger

Hazard statements : H222 Extremely flammable aerosol.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.

Precautionary statements : **Prevention:**  
P210 Keep away from heat/sparks/open flames/hot surfaces.  
No smoking.

## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

P211 Do not spray on an open flame or other ignition source.  
 P251 Pressurized container: Do not pierce or burn, even after use.  
 P261 Avoid breathing spray.  
 P264 Wash skin thoroughly after handling.  
 P271 Use only outdoors or in a well-ventilated area.  
 P280 Wear protective gloves.

### Response:

P302 + P352 IF ON SKIN: Wash with plenty of soap and water.  
 P304 + P340 + P312 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing. Call a POISON CENTER or doctor/ physician if you feel unwell.  
 P332 + P313 If skin irritation occurs: Get medical advice/ attention.  
 P362 Take off contaminated clothing and wash before reuse.

### Storage:

P405 Store locked up.  
 P410 + P412 Protect from sunlight. Do not expose to temperatures exceeding 50 °C/ 122 °F.

### Disposal:

P501 Dispose of contents/ container to an approved waste disposal plant.

### Other hazards which do not result in classification

None known.

## SECTION 3. COMPOSITION/INFORMATION ON INGREDIENTS

Substance / Mixture : Mixture

### Components

Chemical name	CAS-No.	Concentration (% w/w)
Isobutane	75-28-5	>= 30 -< 60
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	>= 10 -< 20
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	< 10
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	< 10
Propane	74-98-6	< 10
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	< 10
Butane	106-97-8	< 10

### Alternative CAS Numbers for some regions

Chemical name	Alternative CAS Number(s)
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	64742-49-0

## SECTION 4. FIRST AID MEASURES

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

- General advice : In the case of accident or if you feel unwell, seek medical advice immediately.  
When symptoms persist or in all cases of doubt seek medical advice.
- If inhaled : If inhaled, remove to fresh air.  
Get medical attention if symptoms occur.
- In case of skin contact : In case of contact, immediately flush skin with plenty of water for at least 15 minutes while removing contaminated clothing and shoes.  
Get medical attention.  
Wash clothing before reuse.  
Thoroughly clean shoes before reuse.
- In case of eye contact : Flush eyes with water as a precaution.  
Get medical attention if irritation develops and persists.
- If swallowed : If swallowed, DO NOT induce vomiting.  
Get medical attention if symptoms occur.  
Rinse mouth thoroughly with water.
- Most important symptoms and effects, both acute and delayed : Causes skin irritation.  
May cause drowsiness or dizziness.
- Protection of first-aiders : First Aid responders should pay attention to self-protection, and use the recommended personal protective equipment when the potential for exposure exists (see section 8).
- Notes to physician : Treat symptomatically and supportively.
- 

**SECTION 5. FIREFIGHTING MEASURES**

- Suitable extinguishing media : Water spray  
Alcohol-resistant foam  
Carbon dioxide (CO<sub>2</sub>)  
Dry chemical
- Unsuitable extinguishing media : High volume water jet
- Specific hazards during fire-fighting : Flash back possible over considerable distance.  
Vapours may form explosive mixtures with air.  
Exposure to combustion products may be a hazard to health.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.
- Hazardous combustion products : Carbon oxides  
Metal oxides
- Specific extinguishing methods : Use extinguishing measures that are appropriate to local circumstances and the surrounding environment.  
Use water spray to cool unopened containers.

## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Remove undamaged containers from fire area if it is safe to do so.  
Evacuate area.

Special protective equipment for firefighters : In the event of fire, wear self-contained breathing apparatus.  
Use personal protective equipment.

Hazchem Code : 2YE

---

### SECTION 6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures : Remove all sources of ignition.  
Use personal protective equipment.  
Follow safe handling advice and personal protective equipment recommendations.

Environmental precautions : Discharge into the environment must be avoided.  
Prevent further leakage or spillage if safe to do so.  
Prevent spreading over a wide area (e.g. by containment or oil barriers).  
Retain and dispose of contaminated wash water.  
Local authorities should be advised if significant spillages cannot be contained.

Methods and materials for containment and cleaning up : Non-sparking tools should be used.  
Soak up with inert absorbent material.  
Suppress (knock down) gases/vapours/mists with a water spray jet.  
For large spills, provide dyking or other appropriate containment to keep material from spreading. If dyked material can be pumped, store recovered material in appropriate container.  
Clean up remaining materials from spill with suitable absorbent.  
Local or national regulations may apply to releases and disposal of this material, as well as those materials and items employed in the cleanup of releases. You will need to determine which regulations are applicable.  
Sections 13 and 15 of this SDS provide information regarding certain local or national requirements.

---

### SECTION 7. HANDLING AND STORAGE

Technical measures : See Engineering measures under EXPOSURE CONTROLS/PERSONAL PROTECTION section.

Local/Total ventilation : If sufficient ventilation is unavailable, use with local exhaust ventilation.  
If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

Advice on safe handling : Do not get on skin or clothing.  
Do not breathe vapours or spray mist.  
Do not swallow.

## HHS Lube 500ml

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
 Date of first issue: 29.09.2010

Avoid contact with eyes.  
 Handle in accordance with good industrial hygiene and safety practice, based on the results of the workplace exposure assessment  
 Keep away from heat and sources of ignition.  
 Take precautionary measures against static discharges.  
 Take care to prevent spills, waste and minimize release to the environment.

Do not spray on an open flame or other ignition source.

- Hygiene measures : If exposure to chemical is likely during typical use, provide eye flushing systems and safety showers close to the working place.  
 When using do not eat, drink or smoke.  
 Wash contaminated clothing before re-use.
- Conditions for safe storage : Store locked up.  
 Keep in a cool, well-ventilated place.  
 Store in accordance with the particular national regulations.  
 Do not pierce or burn, even after use.  
 Keep cool. Protect from sunlight.
- Materials to avoid : Do not store with the following product types:  
 Self-reactive substances and mixtures  
 Organic peroxides  
 Oxidizing agents  
 Flammable liquids  
 Pyrophoric liquids  
 Pyrophoric solids  
 Self-heating substances and mixtures  
 Explosives

### SECTION 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

#### Components with workplace control parameters

Components	CAS-No.	Value type (Form of exposure)	Control parameters / Permissible concentration	Basis
Isobutane	75-28-5	STEL	1,000 ppm	ACGIH
Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane	92128-66-0	TWA	900 mg/m <sup>3</sup>	AU OEL
		TWA (Mist)	5 mg/m <sup>3</sup>	AU OEL
Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics	64742-49-0	TWA (Mist)	5 mg/m <sup>3</sup>	AU OEL
Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics	64742-49-0	STEL	500 ppm 2,050 mg/m <sup>3</sup>	AU OEL
		TWA	400 ppm 1,640 mg/m <sup>3</sup>	AU OEL
		TWA	900 mg/m <sup>3</sup>	AU OEL
		TWA	400 ppm	ACGIH

## HHS Lube 500ml

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
 Date of first issue: 29.09.2010

		STEL	500 ppm	ACGIH
Distillates (petroleum), hydrotreated heavy paraffinic	64742-54-7	TWA (Mist)	5 mg/m <sup>3</sup>	AU OEL
Butane	106-97-8	TWA	800 ppm 1,900 mg/m <sup>3</sup>	AU OEL
		STEL	1,000 ppm	ACGIH

**Engineering measures** : Minimize workplace exposure concentrations.  
 If sufficient ventilation is unavailable, use with local exhaust ventilation.  
 If advised by assessment of the local exposure potential, use only in an area equipped with explosion-proof exhaust ventilation.

### Personal protective equipment

Respiratory protection : If adequate local exhaust ventilation is not available or exposure assessment demonstrates exposures outside the recommended guidelines, use respiratory protection.

Filter type : Self-contained breathing apparatus

### Hand protection

Material : Nitrile rubber  
 Break through time : 480 min  
 Glove thickness : 0.45 mm

Remarks : Choose gloves to protect hands against chemicals depending on the concentration and quantity of the hazardous substance and specific to place of work. For special applications, we recommend clarifying the resistance to chemicals of the aforementioned protective gloves with the glove manufacturer. Wash hands before breaks and at the end of workday.

Eye protection : Wear the following personal protective equipment:  
 Safety glasses

Skin and body protection : Select appropriate protective clothing based on chemical resistance data and an assessment of the local exposure potential.  
 Wear the following personal protective equipment:  
 If assessment demonstrates that there is a risk of explosive atmospheres or flash fires, use flame retardant antistatic protective clothing.  
 Skin contact must be avoided by using impervious protective clothing (gloves, aprons, boots, etc).

## SECTION 9. PHYSICAL AND CHEMICAL PROPERTIES

Appearance : aerosol

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Propellant	:	Isobutane, Propane, Butane
Colour	:	brown
Odour	:	characteristic
Odour Threshold	:	No data available
pH	:	No data available
Melting point/freezing point	:	No data available
Initial boiling point and boiling range	:	-40 °C
Flash point	:	Not applicable
Evaporation rate	:	Not applicable
Flammability (solid, gas)	:	Extremely flammable aerosol.
Upper explosion limit / Upper flammability limit	:	15 %(V)
Lower explosion limit / Lower flammability limit	:	0.6 %(V)
Vapour pressure	:	Not applicable
Relative vapour density	:	Not applicable
Density	:	0.77 g/cm <sup>3</sup> (20 °C) Method: DIN 51757
Solubility(ies) Water solubility	:	insoluble
Partition coefficient: n-octanol/water	:	Not applicable
Auto-ignition temperature	:	> 200 °C
Decomposition temperature	:	No data available
Viscosity Viscosity, kinematic	:	Not applicable
Explosive properties	:	Not explosive
Oxidizing properties	:	The substance or mixture is not classified as oxidizing.

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Particle size : Not applicable

---

**SECTION 10. STABILITY AND REACTIVITY**

Reactivity : Not classified as a reactivity hazard.

Chemical stability : Stable under normal conditions.

Possibility of hazardous reactions : Extremely flammable aerosol.  
Vapours may form explosive mixture with air.  
If the temperature rises there is danger of the vessels bursting due to the high vapor pressure.  
Can react with strong oxidizing agents.

Conditions to avoid : Heat, flames and sparks.

Incompatible materials : Oxidizing agents

Hazardous decomposition products : No hazardous decomposition products are known.

---

**SECTION 11. TOXICOLOGICAL INFORMATION**

Exposure routes : Inhalation  
Skin contact  
Ingestion  
Eye contact

**Acute toxicity**

Not classified based on available information.

**Components:****Isobutane:**

Acute inhalation toxicity : LC50 (Mouse): 260200 ppm  
Exposure time: 4 h  
Test atmosphere: gas

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg

Acute inhalation toxicity : LC50 (Rat): > 5.61 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

Acute dermal toxicity : LD50 (Rabbit): > 2,000 mg/kg

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 4,951 mg/m<sup>3</sup>  
Exposure time: 4 h



## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Test atmosphere: vapour  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 3,160 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Acute oral toxicity : LD50 (Rat): > 5,840 mg/kg  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 23.3 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rat): > 2,800 mg/kg  
Assessment: The substance or mixture has no acute dermal toxicity  
Remarks: Based on data from similar materials

**Propane:**

Acute inhalation toxicity : LC50 (Rat): > 800000 ppm  
Exposure time: 15 min  
Test atmosphere: gas

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Acute oral toxicity : LD50 (Rat): > 5,000 mg/kg  
Method: OECD Test Guideline 401  
Remarks: Based on data from similar materials

Acute inhalation toxicity : LC50 (Rat): > 5.53 mg/l  
Exposure time: 4 h  
Test atmosphere: dust/mist  
Method: OECD Test Guideline 403  
Assessment: The substance or mixture has no acute inhalation toxicity  
Remarks: Based on data from similar materials

Acute dermal toxicity : LD50 (Rabbit): > 5,000 mg/kg  
Method: OECD Test Guideline 402  
Remarks: Based on data from similar materials

**Butane:**

Acute inhalation toxicity : LC50 (Rat): 658 mg/l  
Exposure time: 4 h  
Test atmosphere: vapour

**HHS Lube 500ml**

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
Date of first issue: 29.09.2010

---

**Skin corrosion/irritation**

Causes skin irritation.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Method : OECD Test Guideline 404  
Result : Skin irritation

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit  
Result : Mild skin irritation

Assessment : Repeated exposure may cause skin dryness or cracking.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit  
Result : Skin irritation  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No skin irritation  
Remarks : Based on data from similar materials

**Serious eye damage/eye irritation**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Rabbit  
Result : No eye irritation

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405  
Remarks : Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species : Rabbit  
Result : No eye irritation  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Rabbit  
Result : No eye irritation  
Method : OECD Test Guideline 405

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Remarks : Based on data from similar materials

**Respiratory or skin sensitisation****Skin sensitisation**

Not classified based on available information.

**Respiratory sensitisation**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Test Type	: Maximisation Test
Exposure routes	: Skin contact
Species	: Guinea pig
Result	: negative
Remarks	: Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Test Type	: Buehler Test
Exposure routes	: Skin contact
Species	: Guinea pig
Method	: OECD Test Guideline 406
Result	: negative
Remarks	: Based on data from similar materials

**Chronic toxicity****Germ cell mutagenicity**

Not classified based on available information.

**Components:****Isobutane:**

Genotoxicity in vitro	: Test Type: Chromosome aberration test in vitro Method: OECD Test Guideline 473 Result: negative Remarks: Based on data from similar materials
-----------------------	--

## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (vapour)  
Method: OPPTS 870.5395  
Result: negative

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Genotoxicity in vitro : Test Type: In vitro mammalian cell gene mutation test  
Result: negative  
Remarks: Based on data from similar materials

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Ingestion  
Result: negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Genotoxicity in vitro : Test Type: Chromosome aberration test in vitro  
Result: negative  
Remarks: Based on data from similar materials

Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative  
Remarks: Based on data from similar materials

Test Type: In vitro mammalian cell gene mutation test  
Method: OECD Test Guideline 476  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Method: OECD Test Guideline 474

Result: negative

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Method: OECD Test Guideline 471  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Mouse  
Application Route: Intraperitoneal injection  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Butane:**

Genotoxicity in vitro : Test Type: Bacterial reverse mutation assay (AMES)  
Result: negative

Genotoxicity in vivo : Test Type: Mammalian erythrocyte micronucleus test (in vivo cytogenetic assay)  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 474  
Result: negative  
Remarks: Based on data from similar materials

**Carcinogenicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 102 weeks  
Result : negative

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species : Rat  
Application Route : inhalation (vapour)  
Exposure time : 105 weeks  
Result : negative  
Remarks : Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Species : Mouse  
Application Route : Skin contact  
Exposure time : 78 weeks  
Method : OECD Test Guideline 451  
Result : negative

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Remarks : Based on data from similar materials

**Reproductive toxicity**

Not classified based on available information.

**Components:****Isobutane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: Inhalation  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Effects on fertility : Test Type: Two-generation reproduction toxicity study  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Fertility/early embryonic development  
Species: Rat  
Application Route: inhalation (vapour)  
Result: negative  
Remarks: Based on data from similar materials

**Propane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422

## HHS Lube 500ml

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
Date of first issue: 29.09.2010

---

Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Effects on fertility : Test Type: Reproduction/Developmental toxicity screening test  
Species: Rat  
Application Route: Ingestion  
Result: negative  
Remarks: Based on data from similar materials

Effects on foetal development : Test Type: Embryo-foetal development  
Species: Rat  
Application Route: Skin contact  
Method: OECD Test Guideline 414  
Result: negative  
Remarks: Based on data from similar materials

**Butane:**

Effects on fertility : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Species: Rat  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

Effects on foetal development : Test Type: Combined repeated dose toxicity study with the reproduction/developmental toxicity screening test  
Application Route: inhalation (gas)  
Method: OECD Test Guideline 422  
Result: negative

**STOT - single exposure**

May cause drowsiness or dizziness.

**Components:****Isobutane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Assessment : May cause drowsiness or dizziness.

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Assessment : May cause drowsiness or dizziness.

**HHS Lube 500ml**

Version            Revision Date:            SDS Number:            Date of last issue: 09.09.2019  
6.1                29.11.2019                456561-00004            Date of first issue: 29.09.2010

---

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Assessment                                : May cause drowsiness or dizziness.

**Propane:**

Assessment                                : May cause drowsiness or dizziness.

**Butane:**

Assessment                                : May cause drowsiness or dizziness.

**STOT - repeated exposure**

Not classified based on available information.

**Repeated dose toxicity****Components:****Isobutane:**

Species                                    : Rat  
NOAEL                                     : 9000 ppm  
Application Route                        : inhalation (gas)  
Exposure time                            : 6 Weeks  
Method                                     : OECD Test Guideline 422

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Species                                    : Rat  
NOAEL                                     : > 20 mg/l  
Application Route                        : inhalation (vapour)  
Exposure time                            : 13 Weeks

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Species                                    : Rat  
NOAEL                                     : 10,186 mg/m<sup>3</sup>  
Application Route                        : inhalation (vapour)  
Exposure time                            : 13 Weeks

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Species                                    : Rat  
NOAEL                                     : 12.47 mg/l  
Application Route                        : Inhalation  
Exposure time                            : 90 Days  
Remarks                                  : Based on data from similar materials

**Propane:**

Species                                    : Rat  
NOAEL                                     : 7.214 mg/l  
Application Route                        : inhalation (gas)  
Exposure time                            : 6 Weeks  
Method                                     : OECD Test Guideline 422

**Distillates (petroleum), hydrotreated heavy paraffinic:**



## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Species : Rabbit  
NOAEL : 1,000 mg/kg  
Application Route : Skin contact  
Exposure time : 4 Weeks  
Method : OECD Test Guideline 410  
Remarks : Based on data from similar materials

Species : Rat  
NOAEL : > 980 mg/m<sup>3</sup>  
Application Route : inhalation (dust/mist/fume)  
Exposure time : 4 Weeks

**Butane:**

Species : Rat  
NOAEL : 9000 ppm  
Application Route : inhalation (gas)  
Exposure time : 6 Weeks  
Method : OECD Test Guideline 422

**Aspiration toxicity**

Not classified based on available information.

**Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

The substance or mixture is known to cause human aspiration toxicity hazards or has to be regarded as if it causes a human aspiration toxicity hazard.

---

**SECTION 12. ECOLOGICAL INFORMATION****Ecotoxicity****Components:****Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Toxicity to fish : LL50 (Pimephales promelas (fathead minnow)): 8.2 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction

Toxicity to daphnia and other : EC50 (Daphnia magna (Water flea)): 4.5 mg/l  
aquatic invertebrates : Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202

## HHS Lube 500ml

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
Date of first issue: 29.09.2010

---

Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): 3.1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 0.5 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOELR (Daphnia magna (Water flea)): 2.6 mg/l  
Exposure time: 21 d  
Method: OECD Test Guideline 211

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 10 - 30 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: Based on data from similar materials

Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): > 22 - 46 mg/l  
Exposure time: 48 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 202  
Remarks: Based on data from similar materials

Toxicity to algae/aquatic plants : EL50 (Pseudokirchneriella subcapitata (green algae)): > 1,000 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

NOELR (Pseudokirchneriella subcapitata (green algae)): 1 mg/l  
Exposure time: 72 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 201  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Toxicity to fish : LL50 (Oncorhynchus mykiss (rainbow trout)): > 13.4 mg/l  
Exposure time: 96 h  
Test substance: Water Accommodated Fraction  
Method: OECD Test Guideline 203  
Remarks: No toxicity at the limit of solubility

## HHS Lube 500ml

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

- Toxicity to daphnia and other aquatic invertebrates : EL50 (Daphnia magna (Water flea)): 3 mg/l  
 Exposure time: 48 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EL50 (Selenastrum capricornutum (green algae)): > 10 - 100 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- NOELR (Selenastrum capricornutum (green algae)): 0.1 mg/l  
 Exposure time: 72 h  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 0.17 mg/l  
 Exposure time: 21 d  
 Test substance: Water Accommodated Fraction  
 Method: OECD Test Guideline 211  
 Remarks: Based on data from similar materials

### Distillates (petroleum), hydrotreated heavy paraffinic:

- Toxicity to fish : LC50 (Pimephales promelas (fathead minnow)): > 100 mg/l  
 Exposure time: 96 h  
 Method: OECD Test Guideline 203  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates : EC50 (Daphnia magna (Water flea)): > 10,000 mg/l  
 Exposure time: 48 h  
 Method: OECD Test Guideline 202  
 Remarks: Based on data from similar materials
- Toxicity to algae/aquatic plants : EC50 (Pseudokirchneriella subcapitata (green algae)): > 100 mg/l  
 Exposure time: 72 h  
 Method: OECD Test Guideline 201  
 Remarks: Based on data from similar materials
- Toxicity to daphnia and other aquatic invertebrates (Chronic toxicity) : NOEC (Daphnia magna (Water flea)): 10 mg/l  
 Exposure time: 21 d  
 Method: OECD Test Guideline 211  
 Remarks: Based on data from similar materials
- Toxicity to microorganisms : NOEC: > 1.93 mg/l  
 Exposure time: 10 min  
 Method: DIN 38 412 Part 8  
 Remarks: Based on data from similar materials

**HHS Lube 500ml**

Version 6.1      Revision Date: 29.11.2019      SDS Number: 456561-00004      Date of last issue: 09.09.2019  
Date of first issue: 29.09.2010

---

**Persistence and degradability****Components:****Isobutane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 77.05 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Hydrocarbons, C9-C10, n-alkanes, isoalkanes, cyclics, <2% aromatics:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 89 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Biodegradability : Result: Readily biodegradable.  
Method: OECD Test Guideline 301F  
Remarks: Based on data from similar materials

**Propane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Distillates (petroleum), hydrotreated heavy paraffinic:**

Biodegradability : Result: Not readily biodegradable.  
Biodegradation: 31 %  
Exposure time: 28 d  
Method: OECD Test Guideline 301F

**Butane:**

Biodegradability : Result: Readily biodegradable.  
Biodegradation: 100 %  
Exposure time: 385.5 h  
Remarks: Based on data from similar materials

**Bioaccumulative potential****Components:****Isobutane:**

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Partition coefficient: n-octanol/water : log Pow: 2.8

**Hydrocarbons, C6-C7, n-alkanes, isoalkanes, cyclics, <5% n-hexane:**

Partition coefficient: n-octanol/water : log Pow: 4  
Remarks: Based on data from similar materials

**Hydrocarbons, C7, n-alkanes, isoalkanes, cyclics:**

Partition coefficient: n-octanol/water : log Pow: > 4  
Remarks: Based on data from similar materials

**Butane:**

Partition coefficient: n-octanol/water : log Pow: 2.31

**Mobility in soil**

No data available

**Other adverse effects**

No data available

---

**SECTION 13. DISPOSAL CONSIDERATIONS****Disposal methods**

Waste from residues : Dispose of in accordance with local regulations.

Contaminated packaging : Empty containers should be taken to an approved waste handling site for recycling or disposal.  
Empty containers retain residue and can be dangerous.  
Do not pressurize, cut, weld, braze, solder, drill, grind, or expose such containers to heat, flame, sparks, or other sources of ignition. They may explode and cause injury and/or death.  
If not otherwise specified: Dispose of as unused product.  
Please ensure aerosol cans are sprayed completely empty (including propellant)

---

**SECTION 14. TRANSPORT INFORMATION****International Regulations****UNRTDG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1

**IATA-DGR**

UN/ID No. : UN 1950  
Proper shipping name : Aerosols, flammable  
Class : 2.1

---

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

Packing group : Not assigned by regulation  
Labels : Flammable Gas  
Packing instruction (cargo aircraft) : 203  
Packing instruction (passenger aircraft) : 203

**IMDG-Code**

UN number : UN 1950  
Proper shipping name : AEROSOLS

Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
EmS Code : F-D, S-U  
Marine pollutant : no

**Transport in bulk according to Annex II of MARPOL 73/78 and the IBC Code**

Not applicable for product as supplied.

**National Regulations****ADG**

UN number : UN 1950  
Proper shipping name : AEROSOLS  
Class : 2.1  
Packing group : Not assigned by regulation  
Labels : 2.1  
Hazchem Code : 2YE

**Special precautions for user**

The transport classification(s) provided herein are for informational purposes only, and solely based upon the properties of the unpackaged material as it is described within this Safety Data Sheet. Transportation classifications may vary by mode of transportation, package sizes, and variations in regional or country regulations.

---

**SECTION 15. REGULATORY INFORMATION****Safety, health and environmental regulations/legislation specific for the substance or mixture**

Standard for the Uniform : Schedule 5  
Scheduling of Medicines and  
Poisons

Prohibition/Licensing Requirements : There is no applicable prohibition or notification/licensing requirements, including for carcinogens under Commonwealth, State or Territory legislation.

Volatile organic compounds : Directive 2010/75/EU of 24 November 2010 on industrial emissions (integrated pollution prevention and control)  
Volatile organic compounds (VOC) content: 519 g/l

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

**The components of this product are reported in the following inventories:**

AICS : All ingredients listed or exempt.

---

**SECTION 16. OTHER INFORMATION****Further information**

Revision Date : 29.11.2019

Sources of key data used to compile the Safety Data Sheet : Internal technical data, data from raw material SDSs, OECD eChem Portal search results and European Chemicals Agency, <http://echa.europa.eu/>

Date format : dd.mm.yyyy

**Full text of other abbreviations**ACGIH : USA. ACGIH Threshold Limit Values (TLV)  
AU OEL : Australia. Workplace Exposure Standards for Airborne Contaminants.ACGIH / TWA : 8-hour, time-weighted average  
ACGIH / STEL : Short-term exposure limit  
AU OEL / TWA : Exposure standard - time weighted average  
AU OEL / STEL : Exposure standard - short term exposure limit

AICS - Australian Inventory of Chemical Substances; ANTT - National Agency for Transport by Land of Brazil; ASTM - American Society for the Testing of Materials; bw - Body weight; CMR - Carcinogen, Mutagen or Reproductive Toxicant; DIN - Standard of the German Institute for Standardisation; DSL - Domestic Substances List (Canada); ECx - Concentration associated with x% response; ELx - Loading rate associated with x% response; EmS - Emergency Schedule; ENCS - Existing and New Chemical Substances (Japan); ErCx - Concentration associated with x% growth rate response; ERG - Emergency Response Guide; GHS - Globally Harmonized System; GLP - Good Laboratory Practice; IARC - International Agency for Research on Cancer; IATA - International Air Transport Association; IBC - International Code for the Construction and Equipment of Ships carrying Dangerous Chemicals in Bulk; IC50 - Half maximal inhibitory concentration; ICAO - International Civil Aviation Organization; IECSC - Inventory of Existing Chemical Substances in China; IMDG - International Maritime Dangerous Goods; IMO - International Maritime Organization; ISHL - Industrial Safety and Health Law (Japan); ISO - International Organisation for Standardization; KECI - Korea Existing Chemicals Inventory; LC50 - Lethal Concentration to 50 % of a test population; LD50 - Lethal Dose to 50% of a test population (Median Lethal Dose); MARPOL - International Convention for the Prevention of Pollution from Ships; n.o.s. - Not Otherwise Specified; Nch - Chilean Norm; NO(A)EC - No Observed (Adverse) Effect Concentration; NO(A)EL - No Observed (Adverse) Effect Level; NOELR - No Observable Effect Loading Rate; NOM - Official Mexican Norm; NTP - National Toxicology Program; NZIoC - New Zealand Inventory of Chemicals; OECD - Organization for Economic Co-operation and Development; OPPTS - Office of Chemical Safety and Pollution Prevention; PBT - Persistent, Bioaccumulative and Toxic substance; PICCS - Philippines Inventory of Chemicals and Chemical Substances; (Q)SAR - (Quantitative) Structure Activity Relationship; REACH - Regulation (EC) No 1907/2006 of the European Parliament and of the Council concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals; SADT - Self-Accelerating Decomposition Temperature; SDS - Safety Data Sheet; TCSI - Taiwan Chemical Substance Inventory; TDG - Transportation of Dangerous Goods; TSCA - Toxic Substances Control Act (United States); UN - Unit-

**HHS Lube 500ml**

Version	Revision Date:	SDS Number:	Date of last issue: 09.09.2019
6.1	29.11.2019	456561-00004	Date of first issue: 29.09.2010

---

ed Nations; UNRTDG - United Nations Recommendations on the Transport of Dangerous Goods; vPvB - Very Persistent and Very Bioaccumulative; WHMIS - Workplace Hazardous Materials Information System

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and shall not be considered a warranty or quality specification of any type. The information provided relates only to the specific material identified at the top of this SDS and may not be valid when the SDS material is used in combination with any other materials or in any process, unless specified in the text. Material users should review the information and recommendations in the specific context of their intended manner of handling, use, processing and storage, including an assessment of the appropriateness of the SDS material in the user's end product, if applicable.

AU / EN