



SAFETY DATA SHEET

According to Safe Work Australia Code of Practice on Preparation of Safety Data Sheets for Hazardous Chemicals

SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

1. IDENTIFICATION OF THE SUBSTANCE OR MIXTURE AND OF THE SUPPLIER

Product identifier

Product name RUBIA TIR 9200 FE 5W-30

Other means of identification

Number J6N
Substance/mixture Mixture

Recommended use of the chemical and restrictions on use

Identified uses Motor oil.
Uses advised against Do not use for any purpose other than the one for which it is intended.

Details of the supplier of the safety data sheet

Supplier Total Oil Australia Pty Ltd (ABN 15 149 501 922)
Level 23, 600 Bourke Street, Melbourne,
Victoria 3000 AUSTRALIA
Tel: +61 (3) 9861 8600
Email: lubricants.au@total.com

For further information, please contact:

Contact Point HSE
E-mail Address ms.ap-sds@total.com

Emergency telephone

Australia: +61 2 8014 4558
Asia-Pacific: +65 3158 1074

2. HAZARDS IDENTIFICATION

Classification of the substance or mixture

Not classified as hazardous according to Australia Model Work Health and Safety Regulations

GHS Label elements, including precautionary statements

Signal word None

Hazard Statements



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

None

Other hazards which do not result in classification

Physical-Chemical Properties Contaminated surfaces will be extremely slippery
Environmental properties The product may form an oil film on the water surface that may stop the oxygen exchange.

3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical nature Mineral oil of petroleum origin.

| Chemical Name | CAS-No | EC-No | Weight % |
|--|------------|-----------|----------|
| Distillates (petroleum), hydrotreated heavy paraffinic | 64742-54-7 | 265-157-1 | 40-<50 |
| C14-16-18 Alkyl phenol | ^ | 931-468-2 | 1-<3 |
| Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) | 93819-94-4 | 298-577-9 | 1-<2.5 |

Additional information Product containing mineral oil with less than 3% DMSO extract as measured by IP 346

4. FIRST AID MEASURES

Description of necessary first-aid measures

General advice IN CASE OF SERIOUS OR PERSISTENT CONDITIONS, CALL A DOCTOR OR EMERGENCY MEDICAL CARE.

Eye contact Immediately flush with plenty of water. After initial flushing, remove any contact lenses and continue flushing for at least 15 minutes. Keep eye wide open while rinsing.

Skin contact Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes. Wash contaminated clothing before reuse.

Inhalation Remove casualty to fresh air and keep at rest in a position comfortable for breathing. If not breathing, give artificial respiration.

Ingestion Clean mouth with water. Do NOT induce vomiting. Never give anything by mouth to an unconscious person. Call a physician or Poison Control Center immediately.

Protection of First-aiders First aider needs to protect himself. See Section 8 for more detail. Do not use mouth-to-mouth method if victim ingested or inhaled the substance; induce artificial respiration with the aid of a pocket mask equipped with a one-way valve or other proper respiratory medical device.

Most important symptoms/effects, acute and delayed

Skin contact Not classified based on available data. May produce an allergic reaction.



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

| | |
|--------------------|--|
| Eye contact | Not classified based on available data. |
| Inhalation | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| Ingestion | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |

Indication of immediate medical attention and special treatment needed, if necessary

Notes to physician Treat symptomatically.

5. FIRE-FIGHTING MEASURES

Suitable Extinguishing Media

Suitable Extinguishing Media Carbon dioxide (CO₂). ABC powder. Foam. Water spray or fog.

Unsuitable Extinguishing Media Do not use a solid water stream as it may scatter and spread fire.

Specific hazards arising from the chemical

Special Hazard Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. These may be highly dangerous if inhaled in confined spaces or at high concentration. Combustion products include sulphur oxides (SO₂ and SO₃) and Hydrogen sulphide H₂S, Mercaptans, Phosphorous oxides, Zinc oxides.

Advice for fire-fighters

Special protective equipment for fire-fighters Wear self-contained breathing apparatus and protective suit.

Other information

Cool containers / tanks with water spray. Fire residues and contaminated fire extinguishing water must be disposed of in accordance with local regulations.

6. ACCIDENTAL RELEASE MEASURES

Personal precautions, protective equipment and emergency procedures

General Information Do not touch or walk through spilled material. Contaminated surfaces will be extremely slippery. Use personal protective equipment. Ensure adequate ventilation. Remove all sources of ignition.

Environmental precautions

General Information Do not allow material to contaminate ground water system. Prevent entry into waterways, sewers, basements or confined areas. Local authorities should be advised if significant



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

spillages cannot be contained.

Methods and material for containment and cleaning up

| | |
|--------------------------------|---|
| Methods for containment | Dike to collect large liquid spills. If necessary dike the product with dry earth, sand or similar non-combustible materials. |
| Methods for cleaning up | Dispose of contents/container in accordance with local regulation. In case of soil contamination, remove contaminated soil for remediation or disposal, in accordance with local regulations. |

Other information

| | |
|--------------------------------------|--------------------------------|
| Personal Protective Equipment | See Section 8 for more detail. |
| Waste treatment | See section 13. |

7. HANDLING AND STORAGE

Precautions for safe handling

| | |
|---|--|
| Advice on safe handling | For personal protection see section 8. Use only in well-ventilated areas. Do not breathe vapors or spray mist. Avoid contact with skin, eyes and clothing. |
| Prevention of fire and explosion | Take precautionary measures against static discharges. |
| Hygiene measures | Ensure the application of strict rules of hygiene by the personnel exposed to the risk of contact with the product. When using, do not eat, drink or smoke. Wash hands before breaks and immediately after handling the product. Regular cleaning of equipment, work area and clothing is recommended. Do not use abrasives, solvents or fuels. Do not dry hands with rags that have been contaminated with product. Do not put product contaminated rags into workwear pockets. |

Conditions for safe storage, including any incompatibilities

| | |
|--|--|
| Technical measures/Storage conditions | Keep away from food, drink and animal feedingstuffs. Keep in a banded area. Keep container tightly closed. Keep preferably in the original container. Otherwise reproduce all indication of the regulation label on the new container. Do not remove the hazard labels of the containers (even if they are empty). Design the installations in order to avoid accidental emissions of product (due to seal breakage, for example) onto hot casings or electrical contacts. Store at room temperature. Protect from moisture. |
| Materials to Avoid | Strong oxidizing agents. |

8. EXPOSURE CONTROLS/PERSONAL PROTECTION

Control parameters

| | |
|------------------------|--|
| Exposure limits | Mineral oil mist: USA: OSHA (PEL) TWA 5 mg/m ³ , NIOSH (REL) TWA 5 mg/m ³ , STEL 10 mg/m ³ , ACGIH |
|------------------------|--|



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

(TLV) TWA 5 mg/m³ (highly refined).

Appropriate engineering controls

Engineering Measures

Apply technical measures to comply with the occupational exposure limits. Ensure adequate ventilation, especially in confined areas. When working in confined spaces (tanks, containers, etc.), ensure that there is a supply of air suitable for breathing and wear the recommended equipment.

Individual protection measures, such as personal protective equipment (PPE)

Personal Protective Equipment

General Information

Protective engineering solutions should be implemented and in use before personal protective equipment is considered. The personal protective equipment (PPE) recommendations apply to the product ITSELF. In case of mixtures or formulations, it is suggested that you contact the relevant PPE suppliers.

Respiratory protection

None under normal use conditions. When workers are facing concentrations above the exposure limit they must use appropriate certified respirators. Respirator with combination filter for vapour/particulate (EN 14387): Type A/P1. Warning ! filters have a limited use duration. The use of breathing apparatus must comply strictly with the manufacturer's instructions and the regulations governing their choices and uses.

Eye Protection

Safety glasses with side-shields. EN 166.

Skin and body protection

Wear suitable protective clothing. Protective shoes or boots. Long sleeved clothing. Type 4/6.

Hand Protection

Hydrocarbon-proof gloves: Fluorinated rubber, Nitrile rubber. In case of prolonged contact with the product, it is recommended to wear gloves complying with EN 420 and EN 374 standards, protecting at least for 480 minutes and having a thickness of 0,38 mm at least. These values are indicative only. The level of protection is provided by the material of the glove, its technical characteristics, its resistance to the chemicals to be handled, the appropriateness of its use and its replacement frequency. Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. Also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion, and the contact time.

9. PHYSICAL AND CHEMICAL PROPERTIES

9.1. Information on basic physical and chemical properties

Appearance

limpid



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

| | |
|----------------------|--------------------------|
| Color | yellow |
| Physical State @20°C | liquid |
| Odor | Characteristic |
| Odor Threshold | No information available |

| <u>Property</u> | <u>Values</u> | <u>Remarks</u> | <u>Method</u> |
|------------------------------------|------------------------------|--------------------------|------------------------|
| pH | | Not applicable | |
| Melting point/range | | Not applicable | |
| Boiling point/boiling range | | No information available | |
| Flash point | 220 °C 428 °F | | ASTM D 92 ASTM D 92 |
| Evaporation rate | | No information available | |
| Flammability Limits in Air | | | |
| upper | | No information available | |
| Lower | | No information available | |
| Vapor Pressure | | No information available | |
| Vapor density | | No information available | |
| Relative density | 0.860 | @ 15 °C | ASTM D 1298 |
| Density | 860 kg/m ³ | @ 15 °C | ASTM D 1298 |
| Water solubility | | Insoluble | |
| Solubility in other solvents | | No information available | |
| logPow | | No information available | |
| Autoignition temperature | | No information available | |
| Decomposition temperature | | No information available | |
| Viscosity, kinematic | 72.4 mm ² /s | @ 40 °C | ASTM D 445 |
| Explosive properties | Not explosive | | |
| Oxidizing Properties | Not applicable | | |
| Possibility of hazardous reactions | None under normal processing | | |

9.2. Other information

| | |
|----------------|--------------------------|
| Freezing Point | No information available |
|----------------|--------------------------|

10. STABILITY AND REACTIVITY

| | |
|---|--|
| <u>Reactivity</u> | None under normal processing. |
| <u>Chemical stability</u> | Stable under recommended storage conditions. |
| <u>Possibility of hazardous reactions</u> | No dangerous reaction known under conditions of normal use. |
| <u>Conditions to avoid</u> | Keep away from open flames, hot surfaces and sources of ignition. Keep away from heat and sparks. |
| <u>Incompatible materials</u> | Strong oxidizing agents. |
| <u>Hazardous Decomposition Products</u> | Incomplete combustion and thermolysis may produce gases of varying toxicity such as carbon monoxide, carbon dioxide, various hydrocarbons, aldehydes and soot. Combustion products include sulphur oxides (SO ₂ and SO ₃) and Hydrogen sulphide H ₂ S, Mercaptans, Phosphorous oxides, Zinc oxides. |



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

11. TOXICOLOGICAL INFORMATION**Information on likely routes of exposure**

| | |
|---------------------|--|
| Inhalation | Not classified based on available data. Inhalation of vapors in high concentration may cause irritation of respiratory system. |
| Ingestion | Not classified based on available data. Ingestion may cause gastrointestinal irritation, nausea, vomiting and diarrhea. |
| Skin contact | Not classified based on available data. May produce an allergic reaction. |
| Eye contact | Not classified based on available data. |

Symptoms related to the physical, chemical and toxicological characteristics

| | |
|-----------------|---------------------------|
| Symptoms | No information available. |
|-----------------|---------------------------|

Delayed and immediate effects as well as chronic effects from short and long-term exposure**Acute toxicity - Product Information**

| | |
|--|---|
| Oral | Not classified based on available data. |
| ATEmix (oral) | 77,838.00 mg/kg |
| 0 % of the mixture consists of ingredient(s) of unknown acute oral toxicity | |
| Dermal | Not classified based on available data. |
| ATEmix (dermal) | > 5,000.00 mg/kg |
| 0 % of the mixture consists of ingredient(s) of unknown acute dermal toxicity | |
| Inhalation | Not classified based on available data |
| ATEmix (inhalation-gas) | > 20,000.00 ppm |
| 82.81278 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (gas) | |
| ATEmix (inhalation-vapor) | > 20.00 mg/l |
| 82.81278 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (vapor) | |
| ATEmix (inhalation-dust/mist) | 30.30 mg/l |
| 51.94278 % of the mixture consists of ingredient(s) of unknown acute inhalation toxicity (dust/mist) | |

Acute toxicity - Component Information

| Chemical Name | LD50 Oral | LD50 Dermal | LC50 Inhalation |
|--|---------------------------------------|--|---|
| Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7 | LD50 > 5000 mg/kg bw (rat - OECD 420) | LD50 > 5000 mg/kg bw (rabbit - OECD 402) | LC50 (4h) > 5 mg/l (aerosol) (rat - OECD 403) |
| C14-16-18 Alkyl phenol ^ | LD50 >2000 mg/kg bw (rat) | LD50 >2000 mg/kg bw (rat) | |
| Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4 | LD50 2600 mg/kg (Rat) | LD50 > 3160 mg/kg (Rabbit - OECD 402) | LC50(1h) > 2 mg/l (Rat - OECD Test Guideline 403) |



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

| | |
|--|---|
| Skin corrosion/irritation | Not classified based on available data. |
| Serious eye damage/eye irritation | Not classified based on available data. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required. |
| Sensitization | Not classified based on available data. Contains sensitizer(s). May produce an allergic reaction. The supplier of one or more of the components contained within this formulation has indicated that he has data on the components and/or similar mixtures, which confirms that at the concentration used, classification is not required. |
| Carcinogenicity | Not classified based on available data. During use in engines, contamination of oil with low levels of combustion products occurs. Used motor oils have been shown to cause skin cancer in mice following repeated application and continuous exposure. Brief or intermittent skin contact with used motor oil is not expected to have serious effects in humans if the oil is thoroughly removed by washing with soap and water. |
| Germ Cell Mutagenicity | Not classified based on available data |
| Reproductive toxicity | Not classified based on available data. |
| Target Organ Effects (STOT) | None known |
| STOT - single exposure | Not classified based on available data |
| STOT - repeated exposure | Not classified based on available data |
| Aspiration hazard | Not classified based on available data. |
| Other adverse effects | Characteristic skin lesions (pimples) may develop following prolonged and repeated exposures (contact with contaminated clothing). |

12. ECOLOGICAL INFORMATION

Ecotoxicity

Not classified based on available data.

Acute aquatic toxicity - Product Information

No information available.

Acute aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish | Toxicity to microorganisms |
|---|--|---|--|----------------------------|
| Distillates (petroleum), hydrotreated heavy | EL50 (48h) > 100 mg/l (Pseudokirchnerella) | EL50 (48h) > 10000 mg/l (Daphnia magna - OECD) | LL50 (96h) > 100 mg/l (Oncorhynchus mykiss - | |



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

| | | | | |
|--|---|---|--|--|
| paraffinic 64742-54-7 | subcapitata - OECD 201) | 202) | OECD 203) | |
| C14-16-18 Alkyl phenol ^ | | EC50(48h) > 100 mg/l (Daphnia magna - static - OECD202) | | |
| Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) 93819-94-4 | EbC50 (96h) 2.1 mg/l Selenastrum capricornutum (OECD 201) | EL50 (48h) 5.4 mg/l Daphnia magna (OECD 202) | LC50 (96h) 4.5 mg/l Oncorhynchus mykiss (OECD 203) | |

Chronic aquatic toxicity - Product Information

No information available.

Chronic aquatic toxicity - Component Information

| Chemical Name | Toxicity to algae | Toxicity to daphnia and other aquatic invertebrates | Toxicity to fish | Toxicity to microorganisms |
|--|-------------------|--|---|-------------------------------|
| Distillates (petroleum), hydrotreated heavy paraffinic 64742-54-7 | | NOEL (21d) 10 mg/l (Daphnia magna - QSAR Petrotox) | NOEL (14/28d) > 1000 mg/l (Oncorhynchus mykiss - QSAR Petrotox) | |

Effects on terrestrial organisms No information available.

Persistence and degradability

No information available.

Bioaccumulative potential

Product Information No information available.

logPow No information available

Component Information

| Chemical Name | log Pow |
|---|---------|
| Distillates (petroleum), hydrotreated heavy paraffinic - 64742-54-7 | > 4 |
| Zinc bis[O-(6-methylheptyl)] bis[O-(sec-butyl)] bis(dithiophosphate) - 93819-94-4 | 0.9 |

Mobility

Soil Given its physical and chemical characteristics, the product generally shows low soil mobility.

Air Loss by evaporation is limited.

Water The product is insoluble and floats on water.

Other adverse effects

General Information No information available.



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

13. DISPOSAL CONSIDERATIONS

| | |
|--|---|
| Waste from Residues / Unused Products | Should not be released into the environment. Do not empty into drains. Dispose of in accordance with all applicable national environmental laws and regulations. Where possible recycling is preferred to disposal or incineration. |
| Contaminated packaging | Empty containers should be taken to an approved waste handling site for recycling or disposal. |
| Other information | Refer to section 8 for safety and protective measures for disposal personnel. |

14. TRANSPORT INFORMATION

| | |
|------------------------|---------------|
| <u>ADG (Australia)</u> | Not regulated |
| <u>ADR/RID</u> | Not regulated |
| <u>IMDG/IMO</u> | Not regulated |
| <u>ICAO/IATA</u> | Not regulated |
| <u>ADN</u> | Not regulated |

15. REGULATORY INFORMATION

| | |
|---|--|
| <u>International Inventories</u> | All the substances contained in this product are listed or exempted from listing in the following inventories: Canada (DSL/NDSL) U.S.A. (TSCA) Europe (EINECS/ELINCS/NLP) China (IECSC) Australia (AICS) Korea (KECL) New Zealand (NZIoC) |
|---|--|

National regulatory information

Not classified as hazardous according to Australia Model Work Health and Safety Regulations



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30

Revision Date: 2020-06-29

Version 1.02

16. OTHER INFORMATION

Issuing date: 2016-12-30
Revision Date: 2020-06-29
Revision Note No information available.

Abbreviations, acronyms

ACGIH = American Conference of Governmental Industrial Hygienists
 bw = body weight
 bw/day = body weight/day
 EC x = Effect Concentration associated with x% response
 GLP = Good Laboratory Practice
 IARC = International Agency for Research of Cancer
 LC50 = 50% Lethal concentration - Concentration of a chemical in air or a chemical in water which causes the death of 50% (one half) of a group of test animals
 LD50 = 50% Lethal Dose - Chemical amount, given at once, which causes the death of 50% (one half) of a group of test animals
 LL = Lethal Loading
 NIOSH = National Institute of Occupational Safety and Health
 NOAEL = No Observed Adverse Effect Level
 NOEC = No Observed Effect Concentration
 NOEL = No Observed Effect Level
 OECD = Organization for Economic Co-operation and Development
 OSHA = Occupational Safety and Health Administration
 UVCB = Substance of unknown or Variable composition, Complex reaction products or Biological material
 ATE = Acute Toxicity Estimate
 QSAR = Quantitative Structure-Activity Relationship
 EL50 = median Effective Loading
 NOELR = No Observed Effect Loading Rate
 PAH = Polycyclic aromatic hydrocarbons
 LOEC = Lowest Observed Effect Concentration
 PVA = Polyvinyl alcohol
 PVC = Polyvinyl chloride
 ECOSAR = Ecological Structure Activity Relationships
 CNS = Central nervous system
 EPA = Environmental Protection Agency
 ErL50 = effective loading on growth rate in algae test, to cause a 50% response
 EbL50 = effective loading on growth with the control in algae test, to cause a 50% response
 ADG = Australian Dangerous Goods

Legend:

Section 8

ACGIH - American Conference of Governmental Industrial Hygienists

TWA - Time Weight Average

STEL - Short Term Exposure Limits

S* - Skin notation

| | | | |
|----------|---------------------------|------|-----------------------|
| Ceiling: | Maximum limit value | TWA: | Time weighted average |
| STEL: | Short term exposure limit | * | Skin designation |
| + | Sensitizer | ** | Hazard Designation |
| C | Carcinogen | | |



SDS # : 32496

RUBIA TIR 9200 FE 5W-30

Issuing date: 2016-12-30**Revision Date:** 2020-06-29**Version** 1.02

This safety data sheet serves to complete but not to replace the technical product sheets. The information contained herein is given in good faith and is accurate to the best of knowledge at the date indicated above. It is understood by the user that any use of the product for purposes other than those for which it was designed entails potential risk. The information given herein in no way dispenses the user from knowing and applying all provisions regulating his activity. The user bears sole liability for the precautions required when using the product. The regulatory texts indicated herein are intended to aid the user to fulfil his obligations. This list is not to be considered complete and exhaustive. It is the user's responsibility to ensure that he is subject to no other obligations than those mentioned.

End of the Safety Data Sheet